

## S326 Cleaver

High Precision Optical Fiber Cleaver



### Features and Benefits

- Simple operation
- Easy fiber loading
- Durable and reliable design
- Wide lid opening
- Long blade life
- Light weight (About 30% reduced from previous model)
- High capacity waste bin (S326A)


---

### Product Description

With its ergonomic and light weight design, the S326 cleaver offers the operator the versatility to cleave on a work bench or in the palm of their hand. The reduced lid size and wide opening angle facilitates fiber loading and improves stability resulting in better single and ribbon fiber cleaves. Just pressing the lever completes the fiber cleave and automatically collects the waste. With 24 positions, the long life-time blade achieves numerous cleaves. The S326 cleaver offers optical fiber cleaving for a full range of OSP and OEM applications. The S326A configuration comes with both the regular and large size fiber waste bin or users can choose the smaller S326B option without a bin.



*Operation On Desktop*



*Operation On Hand*



*Wide Lid Opening Angle*

For additional information please contact your sales representative.

You can also visit our website at [www.ofsoptics.com](http://www.ofsoptics.com) or call **1-888-fiberhelp** (1-888-342-3743) USA or **1-770-798-5555** outside the USA.

**Fusion Splicer Customer Service, Training and Service Center**  
 Toll Free: 866-452-9516  
 Phone: 678-783-1090  
 Fax: 678-783-1093  
 Email: [splicers@ofsoptics.com](mailto:splicers@ofsoptics.com)

**OFS Corporate Headquarters**  
 2000 Northeast Expressway  
 Norcross, Georgia 30071, USA  
 Toll Free: 888-Fiber-Help  
 Intl. Phone: 770-798-5555

## S326 Cleaver

### Specifications

| Items                    | Description   |
|--------------------------|---|
| <b>Applicable Fibers</b> | All fiber types   |
| <b>Fiber Count</b>       | Single to 12 ribbon fiber   |
| <b>Clad Diameter</b>     | 125 µm  |
| <b>Coating Diameter</b>  | Single fiber: 250 to 900 µm<br>Ribbon fiber: 280 to 400 µm (thickness)                                |
| <b>Cleave Length</b>     | Single fiber: Fixed length 10 & 16 mm, Variable length 3 to 20 mm<br>Ribbon fiber: Fixed length 10 mm |
| <b>Blade Life *1</b>     | 48000 fibers (2000 fibers×24 positions)   |
| <b>Dimensions</b>        | S326A: 96W×79D×56H mm<br>S326B: 60W×79D×56H mm  |
| <b>Weight</b>            | S326A: 250 g<br>S326B: 195 g  |

### Standard Package

| Items                            | P/N      | Quantity |       |
|----------------------------------|----------|----------|-------|
|                                  |          | S326A    | S326B |
| 1 S326A Main Body                | S326A-01 | 1        | —     |
| 2 S326B Main Body                | S326B-01 | —        | 1     |
| 3 Single Fiber Adapter           | S326X-11 | 1        | 1     |
| 4 Normal Fiber Waste Bin         | S326X-12 | 2        | —     |
| 5 Large Capacity Fiber Waste Bin | S326X-13 | 1        | —     |
| 6 Semi-hard Case                 | S326X-14 | 1        | —     |
| 7 Soft Case                      | S326X-15 | —        | 1     |
| 8 Hexagonal Wrench               | S326X-16 | 1        | 1     |
| Operation Manual                 | FTS-B423 | 1        | 1     |



Copyright © 2018 OFS Fitel, LLC.  
 All rights reserved, printed in USA.

OFS Marketing Communications  
 Doc ID: FITEL-S326  
 Date: 06/18

FITEL is a registered trademark of Furukawa Denki Kogyo Kabushiki Kaisha DBA The Furukawa Electric Co., Ltd Corporation.

DBA Furukawa Electric Co., Ltd.

Furukawa reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any Furukawa warranties or specifications relating to any of its products or services.

