

V-Pin Connectors (Black) for 400/430 µm HCS® P/N: BP05226-02



Overview

The OFS V-System[®] family of HCS 400 μ m fibers, cables and connectors provide a complete optical link solution for use with Avago Versatile Link 650 nm transceivers. Using the advanced optomechanical properties of HCS fiber, the OFS V-System can be connectorized in less than two minutes using a simple crimp and cleave process. No epoxy, no curing, no polishing steps. Quick, easy, reliable.









REMOVE

STRIP

CRIMP

CLEAVE

Typical Applications

Avionics Communications Factory Automation Systems Laser Power Delivery Near-IR Spectroscopy Wind Power Network Controllers



Product Specifications	
Product Description	V-Pin Connectors (Black) for 400/430 µm HCS
Specifications	
For Use with Optical Fiber Cable Types	Step-Index 400/430 µm HCS V-System [®] Cables
Overall Length	1.18 in. (30 mm)
Connector Performance Data	
Insertion Loss @ 650 nm	2.0 dB
Operating Temperature	-40 to +80 °C
Cable Crimp Retention	10 lb. (44.4 N)
Cable Design	
Jacket Diameter	2.2 mm
Compatibility	
Compatible Field Termination Kit	DT03732-34 Crimp & Cleave V-Pin 400 µm Term Kit
Compatible Insertion Loss Kit	P10188-02 V-Pin Insertion Loss Test Kit
Accessories	
V-System Duplex Latch Set	BP04703
V-Pin Mating Adapter	AP04707
Assemblies	

All V-Pin connectors can be provided on respective HCS cable constructions as factory terminated and fully tested assemblies. Please call Technical Support for information at 1-888-438-9936.

Order by Part Number

BP05226-02

For additional information please contact your sales representative.

You can also visit our website at www.ofsoptics.com or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.



Copyright © 2020 OFS Fitel, LLC. All rights reserved, printed in USA.

OFS Marketing Communications Date: 04/20

HCS and V-System are registered trademarks of OFS Fitel, LLC. OFS reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.