


# Loose Tube Fibre Optic Outdoor Cable

8 Element All Dielectric Dry Core Design

**MiDia<sup>®</sup> Dielectric Robust**



Issue March 2017  
according to **OFS Generic Specification**



## Application

Mainly used in Duct-Installation (HD-PE Tubes) and installed by Cable Blowing or Pulling as well as suitable for direct burial into sand beds

## Design

- Optical Fibres
- Gel-filled Buffer Tubes
- Non-metallic Central Member
- Water Blocking Material
- Ripcords
- Layers of Dielectric Strength members
- PE-Jackets

## Features

- PGP Sheath Construction - offers extra mechanical, environmental and rodents protection
- Small tubes for a reduced outer diameter
- Dry Core Design – Cable core water blocked by means of dry “water swellable” technology - for quicker, cleaner cable prep for jointing
- Individual coloured tubes

**Version illustrated is the 96 Fibre Cable**

Fibre Count	Tubes	Core Design	Outer Diameter [mm]	Cable Weight [kg/km]	Standard Length [m]	AT-Code**
84	7	1+8 (1 Filler*)	12.0	125	2000 / 4000 / 6000 / 8000	AT-[ ][ ][ ]25CT-084-Glass
96	8	1+8	12.0	125	2000 / 4000 / 6000 / 8000	AT-[ ][ ][ ]25CT-096-Glass

This table shows nominal diameter and weight values which may differ in shipments.

\*Fillers are natural coloured \*\*Please refer to the OFS AT- Code. The blanks specify the fibre type.

## Identification

**Tube and Fibre Colour Code :**

1	Blue	2	Orange	3	Green	4	Brown	5	Grey	6	White
7	Red	8	Black	9	Yellow	10	Violet	11	Rose	12	Aqua

Alternative tube and fibre colour code available on request

## Sheath Marking:

**OFS OPTICAL CABLE MIDIA DIELECTRIC ROBUST [ID] [MM/YYYY] [Handset Sign] xxxF [Meter Marking]**

Alternative sheath printing available on request.

In case of order the exact sheath printing text will be clarified with the customer.

# Loose Tube Fibre Optic Outdoor Cable

## 8 Element All Dielectric Dry Core Design

### MiDia<sup>®</sup> Dielectric Robust



Issue March 2017  
according to **OFS Generic Specification**

#### Mechanical Properties and Environmental Behaviour

Tests according to IEC 60794

	Parameter	Requirement	Value
<b>Tensile Performance:</b> IEC 60794-1-21-E1	Long term load	- No attenuation increase* - No fibre strain	Load: 800 N
	Short term load, during installation	- No changes in attenuation before versus after load - Max. fibre strain 0.33%	Load: 1.5 x W <i>W is the weight of the cable in N</i>
<b>Crush Performance:</b> IEC 60794-1-21-E3A	Long term load	- No attenuation increase*	Load (Plate / Plate): 500 N
	Short term load	- No changes in attenuation before versus after load - No damage**	Load (Plate / Plate): 2000 N
<b>Bending Performance:</b> IEC 60794-1-21-E11	Handling fixed installed	- No attenuation increase*	Bend radius: 10 x D
	During installation (under load)	- No changes in attenuation before versus after load	Bend radius: 20 x D <i>D is cable diameter</i>
<b>Temperatures:</b> IEC 60794-1-22-F1	Operation	- No attenuation increase*	-30 to +70°C
	Installation		-15 to +60°C
	Storage/Shipping		-40 to +70°C

\*No changes in attenuation means that any changes in measurement value, either positive or negative within the uncertainty of measurement shall be ignored. The total uncertainty of measurement shall be less than or equal to 0.05 dB.

\*\*Mechanical damage – when examined visually without magnification, there shall be no evidence of damage to the sheath. The imprint of plates will not be considered as damage.

#### Shipping Information

Cable Length	Drum Dimensions (approx.)		Shipping Weight (calc.)	
	Diameter(battened)	Width	Without lagging	With lagging
2000 m	1250 mm	790 mm	330 kg	370 kg
4000 m	1450 mm	790 mm	610 kg	650 kg
6000 m	1600 mm	1055 mm	880 kg	940 kg
8000 m	1750 mm	1055 mm	1150 kg	1210 kg

The shipping information are given for one-way reels. Reusable reels are available on request.

The information is believed to be accurate at time of issue.  
OFS reserves the right to improve, enhance and modify the features and specifications of OFS products without prior notification.  
Please ensure you have the latest version of the data sheet.

This data sheet is property of OFS.  
For additional information please contact your sales representative.  
You can also visit our

website at <http://www.ofsoptics.com>.

Telephone: +49 (0) 228 7489 201

Email: [cableinfo@ofsoptics.com](mailto:cableinfo@ofsoptics.com)

