


Loose Tube Fibre Optic Outdoor Cable

24 Element All Dielectric Dry Core Design

Standard Dielectric Robust



Issue May 2017
according to **OFS Generic Specification**



Application

Mainly used in Duct-Installation (HD-PE Tubes) and installed by Cable Blowing or Pulling as well as suitable for direct burial into sand beds

Design

- Optical Fibres
- Gel-filled Buffer Tubes
- Non-metallic Central Member
- Water Blocked Cable Core
- Ripcords
- Inner PE-Jacket
- Layers of non-metallic Glass Elements
- Outer PE-Jacket

Features

- PGP (Polyethylene -Glass- Polyethylene) Sheath Construction - offers extra mechanical, environmental and rodents protection
- Dry Core Design – Cable core water blocked by means of dry “water swellable” technology - for quicker, cleaner cable prep for jointing
- Individual coloured tubes

Version illustrated is the 288 Fibre Cable

Fibre Count	Tubes	Core Design	Outer Diameter [mm]	Cable Weight [kg/km]	Standard Length [m]	AT-Code**
216	18	1+24 (6 Fillers*)	19.3	290	2000 / 4000	AT-[][][]22UT-216-Glass
240	20	1+24 (4 Fillers*)	19.3	290	2000 / 4000	AT-[][][]22UT-240-Glass
264	22	1+24 (2 Fillers*)	19.3	290	2000 / 4000	AT-[][][]22UT-264-Glass
288	24	1+24	19.3	290	2000 / 4000	AT-[][][]22UT-288-Glass

This table shows nominal diameter and weight values which may differ in shipments.

*Fillers are natural coloured **Please refer to the OFS AT- Code. The blanks specify the fibre type.

Identification

Fibre Colour Code:

1	Blue	2	Orange	3	Green	4	Brown	5	Grey	6	White
7	Red	8	Black	9	Yellow	10	Violet	11	Rose	12	Aqua

Alternative fibre colour code available on request

Tube Colour Code:

1+10+22	Blue	2+11+23	Orange	3+12+24	Green	4+13	Brown	5+14	Grey	6+15	White
7+16	Red	8+17	Black	9+18	Yellow	19	Violet	20	Rose	21	Aqua

Alternative tube colour code available on request

Loose Tube Fibre Optic Outdoor Cable

24 Element All Dielectric Dry Core Design

Standard Dielectric Robust



Issue May 2017
according to **OFS Generic Specification**

Sheath Marking:

OFS OPTICAL CABLE STANDARD DIELECTRIC ROBUST [ID] [MM/YYYY] [Handset Sign] xxxF [Meter Marking]

Alternative sheath printing available on request.

In case of order the exact sheath printing text will be clarified with the customer.

Mechanical Properties and Environmental Behaviour

Tests according to **IEC 60794**

	Parameter	Requirement	Value
Tensile Performance: IEC 60794-1-21 E1	Long term load	- No attenuation increase* - No fibre strain	Load: 1000 N
	Short term load, during installation	- No changes in attenuation before versus after load - Max. fibre strain 0.33%	Load: 2700 N
Crush Performance: IEC 60794-1-21-E3A	Long term load	- No attenuation increase*	Load (Plate / Plate): 500 N
	Short term load	- No changes in attenuation before versus after load - No damage**	Load (Plate / Plate): 3000 N
Bending Performance: IEC 60794-1-21-E11	Handling fixed installed	- No attenuation increase*	Bend radius: 10 x D
	During installation (under load)	- No changes in attenuation before versus after load	Bend radius: 20 x D <i>D is cable diameter</i>
Temperatures: IEC 60794-1-22-F1	Operation	- No attenuation increase*	-40 to +70°C
	Installation		-15 to +60°C
	Storage/Shipping		-40 to +70°C

*No changes in attenuation means that any changes in measurement value, either positive or negative within the uncertainty of measurement shall be ignored. The total uncertainty of measurement shall be less than or equal to 0.05 dB.

** Mechanical damage – when examined visually without magnification, there shall be no evidence of damage to the sheath. The imprint of plates will not be considered as damage.

Shipping Information

Cable Length	Drum Dimensions (approx.)		Shipping Weight (calc.)	
	Diameter(battened)	Width	Without lagging	With lagging
2000 m	1600 mm	1055 mm	710 kg	770 kg
4000 m	2050 mm	1100 mm	1340 kg	1420 kg

The shipping information are given for one-way reels. Reusable reels are available on request.

The information is believed to be accurate at time of issue.

OFS reserves the right to improve, enhance and modify the features and specifications of OFS products without prior notification.

Please ensure you have the latest version of the data sheet.

This data sheet is property of OFS.

For additional information please contact your sales representative.

You can also visit our

website at <http://www.ofsoptics.com>.

Telephone: +49 (0) 228 7489 201

Email: cableinfo@ofsoptics.com

