

200-22 HCL Optical Fiber

P/N: BF06856-01



Overview

The OFS family of High-Power Delivery optical fibers includes the HCL product line. HCL fibers are low-OH, all-silica fibers coated with HCS® fluoroacrylate to improve fiber strength and to reduce static fatigue. ETFE is used as the outer buffer on these step-index, multimode fibers. They have a nominal NA of 0.22 and are available in a variety of core sizes and core/clad ratios.

Typical Applications

Cascaded Laser Power Delivery
High-Power Laser Delivery
Industrial Cabling
Laser Surgery
Laser Welding and Cutting
Near-IR (up to 2100 nm)
Laser Power Delivery





Product Specifications	
Product Description	200-22 HCL
Physical Characteristics	
Core Diameter	200 ± 5 μm
Cladding Diameter	240 ± 5 μm
Hard Coating Diameter	260 ± 5 μm
Buffer Diameter	375 ± 30 μm
Clad/Coating Offset	7 μm
Crimp & Cleave Compatible	Yes
Buffer Material	ETFE
Standard Buffer Color	Blue
Coating Material	HCS® Fluoroacrylate
Optical Characteristics	
Туре	Multimode Step-Index
Numerical Aperture	0.22 ± 0.02
Attenuation @ 850 nm	≤ 8 dB/km
Water Content	Low OH
Mechanical and Environmental	
Operating Temperature	-65 to +125 °C
Short-Term Bend Radius	≥ 9 mm
Long-Term Bend Radius	≥ 14 mm
Proof Test Level	≥ 200 kpsi (0.689 GPa)
Order by Part Number	BF06856-01
Product Description Code	272-22 HCL

OPTIONS: Cabling, Carbon Coating, Clad Diameter, Connectorization, Core Diameter, Low Bioburden Packaging and Manufacturing, Metalization, Numerical Aperture, Buffer Colors, Proof Test

For additional information please contact your sales representative.

You can also visit our website at www.ofsoptics.com or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.







OFS Marketing Communications

Date: 12/19