




ClearLite® 630 11 Short Wavelength Optical Fiber

P/N: CF04247-02



Overview

OFS ClearLite 630 11 operates at 630 nm and has an NA of 0.11. The fiber has a dual UV acrylate coating. Short wavelength fibers perform in a wide variety of applications, some requiring visible light.

Light sources for this fiber can be LEDs, laser diodes, visible lamps, or gas lasers.

Typical Applications

- DWDM Components
- EDFAs
- Sensors and Communications Systems
- Short Wavelength Laser and LED Sources

Product Specifications

Product Description	ClearLite 630 11 Short Wavelength Optical Fiber
Physical Characteristics	
Coating Material	Dual UV Acrylate
Core Diameter (Nominal)	3.9 μm
Cladding Diameter	125 \pm 1 μm
Coating/Buffer Diameter	250 \pm 10 μm
Clad Non-Circularity	\leq 2.0%
Core/Clad Offset	\leq 0.5 μm
Optical Characteristics	
Type	Single-Mode
Operating Wavelength	630 nm
Cutoff Wavelength	580 \pm 40 nm
Mode Field Diameter @ 630 nm	4.3 \pm .75 μm
Attenuation @ 630 nm	\leq 12 dB/km
Numerical Aperture (Nominal)	0.11
Mechanical and Environmental	
Operating Temperature	-40 to +85 $^{\circ}\text{C}$
Short-Term Bend Radius	\geq 5 mm
Long-Term Bend Radius	\geq 9 mm
Proof Test Level	200 kpsi (1.38 GPa)
Order by Part Number	CF04247-02
Product Description Code	SMC-A0630B
OPTIONS: Buffer Color, Buffer Material, Buffer Size, Cutoff Wavelength, Metalization, Proof Test, Termination	

For additional information please contact your sales representative.

You can also visit our website at www.ofsoptics.com
or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.



FURUKAWA
SOLUTIONS

For a full list of
our certifications,
visit our website.



Copyright © 2024 OFS Fitel, LLC.
All rights reserved, printed in USA.

OFS Marketing Communications
Date: 03/24

ClearLite is a registered trademark of OFS Fitel, LLC.
OFS reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.