


400 μm PYROCOAT[®] Step-Index Optical Fiber

P/N: CF04406-06



Overview

High OH concentration in these fibers results in efficient power transmission in the wavelength range from high UV through visible light. The all-silica base construction also creates a high damage threshold and high-performance optical properties.

High temperature environments require the use of PYROCOAT[®] polyimide coating.

Typical Applications

- Illumination
- Laser Surgery
- Radiation Analysis
- Sensors
- UV Fluorescence
- UV Spectroscopy

Product Specifications	
Product Description	400 μ m PYROCOAT Step-Index
Physical Characteristics	
Core Diameter	400 \pm 10 μ m
Cladding Diameter	440 \pm 10 μ m
Coating Diameter	470 \pm 5 μ m
Coating Concentricity	\geq 80%
Crimp & Cleave Compatible	No
Coating Material	PYROCOAT
Optical Characteristics	
Type	Multimode Step-Index
Numerical Aperture	0.22
Attenuation @ 820 nm	\leq 10 dB/km
Water Content	High OH
Mechanical and Environmental	
Operating Temperature	-65 to +300 $^{\circ}$ C
Short-Term Temperature Excursions	Up to 400 $^{\circ}$ C
Short-Term Bend Radius	\geq 66 mm
Long-Term Bend Radius	\geq 112 mm
Proof Test Level	\geq 100 kpsi (0.689 GPa)
Order by Part Number	CF04406-06
Product Description Code	TCG-MA400H
OPTIONS: Clad Diameter, Core Diameter, Connectorization, Numerical Aperture, Metalization, Proof Test	
NOTE: OFS polyimide optical fibers are known to operate in environments up to 300 $^{\circ}$ C. Performance is application dependent. Contact our Technical Sales department to discuss your specific application requirements. 1-860-678-6636	

For additional information please contact your sales representative.

You can also visit our website at www.ofsoptics.com or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.



Copyright © 2019 OFS Fitel, LLC.
All rights reserved, printed in USA.

OFS Marketing Communications
Date: 12/19



HCS and PYROCOAT are registered trademarks of OFS Fitel, LLC. OFS reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.