

EZ-Bend® Fast Wrap Solution



External View



Internal View

Features

- Stores up to 150 feet of 3 mm drop cable for running indoors and/or outdoors
- Wall-mount Network Interface Device (NID) that is provided with preloaded SCA EZ-Bend® Drop Assembly to simplify installation at the customer premise

Product Description

The EZ-Bend Fast Wrap Solution is designed for mounting on a wall as a Network Interface Device (NID) to transition from rigid outside plant cable to a flexible drop cable for wrapping around a house as well as for internal routing to the ONT.

- Secured with 3/8" Hex bolt
- Support entry with a miniLT flat or round type cables
- EZ-Bend 3 mm drop can be wrapped out the outside as needed before entry into customer location, and then routed within the building.



Product Characteristics

Capacity	Up to 150 feet of EZ-Bend 3 mm drop cable Configured with 1 SCA adapter Splicing - slot for 1 fusion splice	
Protection Level	IP 55, designed to GR-771	
Application Environment	Outdoor application in wall mount	
Adapter Type	SCA drop assembly and adapter loaded into the standard configuration	
Drop Characteristics	Configured with up to 150' of 3 mm EZ-Bend drop cable terminated with SCA connectors	
Physical Characteristics		
Terminal Dimensions	223 (width) x 231 (height) x 73.7 (depth) mm 8.8 (width) x 9.1 (height) x 2.9 (depth) inches	
Drop Cable Dimensions	3 mm round type	
Body Material	UV-Rated Plastic (PC + ABS), UL94V-0	
Color	Light grey	
Operation Temperature	-40 °C to 70 °C	
Sealing System for Drop Cables	Mechanical	

Ordering Information		
Comcode	Product Code	Description
301181012	SLIMBOX-OUTDOOR NID-D-SCASCA-SPOOL-100F	Outdoor NID with integrated EZ-BEND SCA assembly, 100 feet
301181020	SLIMBOX-OUTDOOR NID-D-SCASCA-SPOOL-150F	Outdoor NID with integrated EZ-BEND SCA assembly, 150 feet

For additional information please contact your sales representative.

You can also visit our website at www.ofsoptics.com

or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.



Copyright © 2023 OFS Fitel, LLC. All rights reserved, printed in USA. OFS Marketing Communications DOC ID: fap-422 Date: 08/23

EZ-Bend is a registered trademark of OFS Fitel, LLC. OFS reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.