

S317 Cleaver

3-Step Single Fiber Cleaver





Features and Benefits

- · Simple operation
- · Easy fiber loading
- Wide lid opening
- Long blade life
- High precision

Product Description

The FITEL S317 Cleaver brings excellent value for a high precision cleaver and is designed for optical fiber cleaving for a full range of OSP and OEM applications.

For additional information please contact your sales representative.

You can also visit our website at www.ofsoptics.com or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.

Fusion Splicer Customer Service, Training and Service Center

Toll Free: 866-452-9516 Phone: 678-783-1090 Fax: 678-783-1093

Email: splicers@ofsoptics.com

OFS Corporate Headquarters

2000 Northeast Expressway Norcross, Georgia 30071, USA Toll Free: 888-Fiber-Help Intl. Phone: 770-798-5555

Specifications

Items	Description
Applicable Fibers	All fiber types
Fiber Count	Single
Clad Diameter	125 μm
Coating Diameter	250 to 900 μm
Cleave Length	5-16 mm for 250 μm and 10-16 mm for 900 μm
Blade Life	48,000 fibers (3000 fibers X 16 positions)
Dimensions	3.1"W × 3.6"D × 1.5"H
Weight	13oz.
Cutting Angle	≤ 0.5*

^{*} Typical value when cleaving with the method and fiber specified by FEC.

Standard Package

Items	P/N
S317	-
Single Fiber Adapter	S317X-02
Manual	FTS-B607
Case	S317X-04
Hexagon Wrench	-





Copyright © 2021 OFS Fitel, LLC. All rights reserved, printed in USA.

OFS Marketing Communications Doc ID: FITEL-S317

Doc ID: FITEL-S317 Date: 10/21

FITEL is a registered trademark of Furukawa Denki Kogyo Kabushiki Kaisha DBA The Furukawa Electric Co., Ltd Corporation.

DBA Furukawa Electric Co., Ltd.

Furukawa reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any Furukawa warranties or specifications relating to any of its products or services.