


1540 Highly-Non-Linear Optical Fiber

P/N: HNLF-SPINE ZDW 1540



Overview

OFS Highly-Non-Linear Optical Fiber (HNLF) combines a high non-linear coefficient with a small dispersion slope. The fiber design includes a high delta core, doped with GeO₂, surrounded by a deeply depressed ring doped with fluorine.

HNLF is available in five versions: HNLF Standard with a dispersion slope of 0.019 ps/(nm²·km), HNLF Zero-slope with a dispersion slope of 0.006 ps/(nm²·km), HNLF-PM which is polarization maintaining, HNLF Al-Doped with an aluminum doped core for increased SBS threshold, and HNLF-SPINE (Stable Phase-matching for Improved Nonlinear Efficiency) with a zero dispersion wavelength that is very stable along the fiber length. All are available with wide range dispersion values.

Typical Applications

Parametric Process



A Furukawa Company

1540 Highly-Non-Linear Optical Fiber

P/N: HNFL-SPINE ZDW 1540

Product Specifications	
Product Description	1540 Highly-Non-Linear Optical Fiber
Optical Characteristics	
Type	Non-Standard
Fiber Length	50 to 2000 m
Fiber Length Tolerance	± 3 m
Cutoff Wavelength	< 1525 nm
Effective Area (Typical)	14.4 μm ²
Zero Dispersion Wavelength	1526 to 1543 nm
Dispersion	0.4 to 1.8 ps/(nm·km)
Dispersion Slope (Typical)	0.071 ps/(nm ² ·km)
PMD	≤ 0.20 ps/√km
Attenuation	≤ 0.90 dB/km
Attenuation (Typical)	0.83 dB/km
Splice Loss to SSMF Pigtail	≤ 0.20 dB
Splice Loss to SSMF Pigtail (Typical)	0.10 dB
SBS Threshold x Effective Length (Typical)	30 W·m
Non-Linear Coefficient (Typical)	9.3 W ⁻¹ ·km ⁻¹

Ordering Information for HNFL-SPINE ZDW 1540 Module	
Short (1-2 meter) Standard Single-Mode (SSMF) pigtails with connectors are spliced to the HNFL. The fiber with pigtails is delivered on a 29 x 175 mm spool covered with a protective layer of silicone glue.	
Ordering Code: HNFL-Z1L-LLLL-P-M-DD	
Length Code (LLLL)	Length in step of 50 meters (0050, 0100, 0150, .. 2000)
Pigtail Option (P)	Pigtail Type 1 = SSMF with FC/APC Connectors 2 = SSMF with FC/PC Connectors
Mechanical Option (M)	Mechanical Package 1 = 29x175 mm spool with silicone glue 2 = 29x175 mm spool without silicone glue
Dispersion Code (DD)	Dispersion at 1550 nm (ps/nm·km) z0 = 0.0 ± 1.0 p1 = 1.0 ± 1.0

Ordering Information for HNFL-SPINE ZDW 1540 Fiber	
The HNFL fiber can also be delivered without pigtails on a 105 x 265 mm spool without any silicone. However, please note that splice loss of about 1 dB from HNFL to SSMF must be expected when using standard fusion splicers.	
Item Number	Dispersion at 1550 nm (ps/nm·km)
80416z0	0.0 ± 1.0
80416p1	1.0 ± 1.0

For additional information please contact your sales representative.

You can also visit our website at www.ofsoptics.com or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.



Copyright © 2023 OFS Fitel, LLC. All rights reserved, printed in USA.

OFS Marketing Communications
Date: 02/23

For a full list of our certifications, visit our website.



OFS reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.