




## InvisiLight® EZ-Connect Module

Pre-terminated FTTx Module for Easy Deployment in Living Unit



**InvisiLight EZ-Connect Module**  
External View



Internal View

### Key Features

- Handles 900  $\mu\text{m}$  InvisiLight Optical Fiber and the slack management for Tight Buffer Optical Fiber and the ONT jumper
- Wall mounted compact module
- Allows up to 40 meters to be dispensed on the bottom layer and up to 2.5 meters of 2 mm cord on the top spool layer (up to 1.5 meters considering a 3 mm cord)
- Spool locking system to facilitate the jumper spooling out
- RoHS-compliant; free from heavy metals and environmentally friendly

### Product Description

The InvisiLight EZ-Connect Module is provided with an integrated jumper to connect to the ONT. This jumper is available in two versions: 2 mm or 3 mm Outside Diameter with 2.5 and 1.5 meter lengths respectively. The InvisiLight tight buffer optical fiber exits on one of the four module corners. The module has an internal parking space for the inside SC connector end. The internal spool allows slack management of the tight buffer and jumper and may be locked in order to spool out by hand the desired length of jumper. The bottom layer of the spool supports up to 40 meters of InvisiLight tight buffer optical fiber.



## InvisiLight® EZ-Connect Module

InvisiLight EZ-Connect Module Specifications	
Product Characteristics	
<b>Connector Type</b>	SC connector on inside and outside end
<b>Polishing Type</b>	APC
<b>Fiber Type</b>	BLI-A/B - G.657.B3
<b>Bottom Layer (Max. Length)</b>	40 meters
<b>Splice Repair</b>	Yes (2 splices)
<b>Top Layer (Max. Length)</b>	5 meters of tight buffer fiber 2.5 meters of 2 mm cord 1.5 meters of 3 mm cord
<b>Module Dimensions</b>	3.45" x 3.13" x 1.41" 87.68 x 79.56 x 35.74 mm
<b>Material</b>	Plastic, UL94V-0
<b>Color</b>	White
<b>Operating Temperature</b>	-40 to +85 °C
<b>Storage Temperature</b>	-40 to +85 °C
Optical Characteristics	
<b>Insertion Loss</b>	≤0.30 dB - maximum
<b>Return Loss</b>	≥60 dB

Ordering Information		
Comcode	Product Code	Description
301141818	NVSLGHTD-D-SCASCA-1-NAM-KIT 900-5.0M/40M	EZ-Connect module with 5.0 meters of 900 μm fiber on the top layer and 40 meters of 900 μm fiber on the bottom layer; pre connectorized both ends with SCA connectors
301141826	NVSLGHTD-D-SCASCA-1-NAM-KIT 2MM-2.5M/40M	EZ-Connect module with 2.5 meters of 2.0 mm fiber on the top layer and 40 meters of 900 μm fiber on the bottom layer; pre connectorized both ends with SCA connectors
301141834	NVSLGHTD-D-SCASCA-1-NAM-KIT 3MM-1.5M/40M	EZ-Connect module with 1.5 meters of 3.0 mm fiber on the top layer and 40 meters of 900 μm fiber on the bottom layer; pre connectorized both ends with SCA connectors

For additional information please contact your sales representative.

You can also visit our website at [www.ofsoptics.com](http://www.ofsoptics.com) or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.



Copyright © 2025 OFS Fitel, LLC.  
All rights reserved, printed in USA.

OFS Marketing Communications  
DOC ID: fap-312 Date: 01/25

For a full list of our certifications, visit our website.



InvisiLight is a registered trademark of OFS Fitel, LLC. OFS reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.