



## InvisiLight® Indoor/Outdoor POE Module



External View



Internal View



Internal View with Spool

### Key Features

- Compact for discrete installation (Daisy chain installation with InvisiLight Facade fiber optic cables)
- Compatible with the InvisiLight 1- or 2-Fiber ILU Solution
- Wall mounted
- In-line installation for indoor applications with the OFS HomeRun cable
- Generous amount of slack storage in compact space

### Product Description

The InvisiLight Indoor/Outdoor POE Module is a facade mountable customer connection point used to connect feeder cables in the access network to drop cables reaching into the premises. The applications include Fiber to the Home, Building, or Apartment. It is compatible with an enables connecting the InvisiLight Facade 12 and 24 fiber optic cables to the InvisiLight ILU Plug-and-Play Solution. The internal connection between the InvisiLight ILU spool and the InvisiLight Facade fiber optic cable is made with a pigtail splice or field mounted connectors.

The module accepts one InvisiLight ILU spool up to 20 meters which eliminates the need for a wall mounted module inside the customer premises. The module has two split grommets at the bottom which enables quick and easy installation of the InvisiLight Facade 3.0 or 3.8 mm multifiber feeder cable.

The InvisiLight Outdoor module can be wall mounted indoors or outdoors. Two basic configurations of the module are available:

- Stand alone with the InvisiLight spool
- The InvisiLight Facade 12-Fiber or 24-Fiber cable is supplied as a bulk cable
- Kit version: The InvisiLight Facade 12-Fiber or 24-Fiber multifiber cable is pre-connectorized on the network end, and supplied with 12- or 24-Fiber outdoor modules; additional components like InvisiLight spools and pigtails may be included in the kit

The outdoor module can support InvisiLight Facade 3.0 or 3.8 mm fiber optic cable and a 3.0 or 4.8 mm drop grommet.

- Grommet for 3.0 mm feeder or drop cable
- Grommet for 3.8 mm feeder cable
- Grommet for 4.8 mm drop cable



## InvisiLight® Indoor/Outdoor POE Module

InvisiLight® Indoor/Outdoor POE Module Specifications	
Product Characteristics	
<b>Capacity</b>	Up to 2 SC ports and 2 splices
<b>Protection Level</b>	IP 55
<b>Application Environment</b>	Outdoor application in facade installation; In line installation in indoor application
<b>Adapter Type</b>	SC
Physical Characteristics	
<b>Terminal Dimensions (W x H x D)</b>	196 mm* x 112 mm x 38 mm (7.7 in* x 4.4 in x 1.5 in) *Includes the length of the mounting wings. Box is 154 mm (6" wide)
<b>Feeder Cable Dimensions</b>	3 mm or 3.8 mm diameter round
<b>Material</b>	Polypropylene, UL 94V-0, gray color
<b>Operating Temperature</b>	-40 °C to 60 °C
<b>Sealing System for Feeder Cables</b>	Mechanical grommets for 3.0 or 3.8 mm

InvisiLight Indoor/Outdoor POE Module Ordering Information		
Comcode	Product Code	Description
301146866	NVSLGHTFIO-POE MODULE 1 SCA ADPT-02	InvisiLight Indoor/Outdoor POE Module with 1 SCA Simplex adapter
301150579	NVSLGHTFIO-POE MODULE 2 SCA ADPT-02	InvisiLight Indoor/Outdoor POE Module with 2 SCA Simplex adapters
301146858	NVSLGHTFIO-POE MODULE 1 LCA ADPT-02	InvisiLight Indoor/Outdoor POE Module with 1 LCA Duplex adapter
301150561	NVSLGHTFIO-POE MODULE 2 LCA ADPT-04	InvisiLight Indoor/Outdoor POE Module with 2 LCA Duplex adapters
301146841	NVSLGHTFIO-POE MODULE INSIDE ADAPTER	InvisiLight Indoor/Outdoor POE Module without adapter

For additional information please contact your sales representative.

You can also visit our website at [www.ofsoptics.com](http://www.ofsoptics.com)  
or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.



**FURUKAWA**  
SOLUTIONS

Copyright © 2024 OFS Fitel, LLC.  
All rights reserved, printed in USA.

OFS Marketing Communications  
DOC ID: fap-314 Date: 09/24

For a full list of  
our certifications,  
visit our website.



InvisiLight is a registered trademark of OFS Fitel, LLC.  
OFS reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.