




Sherpa CMS™ ADSS Cable Management System

Installation System for ADSS Networks



Sherpa Cable Manager

Features and Benefits

- A patent-pending dielectric system enabling attachment of dielectric drop cables to ADSS trunk cables
- Can significantly reduce make-ready for some networks
- For many networks, can significantly speed installation in comparison to strand and lashed networks deployed from scratch
- Tested for reliability impact
- Can increase drop cable ranges by trunk cables
- Can reduce effective span length and sags when applied to a neutral
- EPDM rubber for long-term reliability
- Fast and easy installation
- Aesthetically clean



ADSS to Flat Drop



Strand to Mini Flat Drop



ADSS to Round Drop





Neutral to ADSS

Product Description

The Sherpa CMS ADSS Cable Management System is a non-metallic (EPDM rubber) way to attach cables on a span.


There are different versions:

1. Attach flat and/or round drops to ADSS trunk cables to simplify ADSS-based fiber-optic networks, primarily for electrical coop and municipal FTTH applications.
2. Attach ADSS trunk cables to a neutral or other metallic messengers to decrease effective ADSS span lengths and sag under load
3. Attach 2 ADSS trunk cables together





Sherpa CMS™ Cable Management System



Sherpa CMS attachments are designed and manufactured for specific cable combinations. If the combination of interest is not included below, please contact OFS. New combinations can be developed as appropriate.

Sherpa CMS may affect span length recommendations for a given combination of cables. Please contact OFS or your cable manufacturer for more information.

Ordering Information - Sherpa CMS Installation System



Four FLAT drop slots				
ADSS Diameter Range	11.7-11.8 mm	12.7-12.8 mm	14.7-14.8 mm	18.5-18.6 mm
OFS Comcode	301172300	301172318	301172326	301172334
Description	SHERPA-11.8MM-FLAT-4	SHERPA-12.8MM-FLAT-4	SHERPA-14.8MM-FLAT-4	SHERPA-18.6MM-FLAT-4



Eight mini FLAT drop slots				
Strand Diameter	7.94 mm – Contact OFS for other versions.			
OFS Comcode	301178778			
Description	SHERPA-7.9MM-RFLAT-8			



Four ROUND drop slots				
ADSS Diameter Range (mm)	11.7-11.8 mm	12.7-12.8 mm	14.7-14.8 mm	18.5-18.6 mm
OFS Comcode	TBD	TBD	TBD	TBD



Slots for ADSS				
ADSS Diameter Range	11.7-11.8 mm	12.7-12.8 mm	14.7-14.8 mm	18.5-18.6 mm
OFS Comcode	TBD	TBD	TBD	TBD



Slots for neutral				
Neutral Diameter Range	.325 (8.3) in 354" (9.0) mm			

CUSTOM SIZES ARE READILY AVAILABLE UPON REQUEST.

For additional information please contact your sales representative.

You can also visit our website at www.ofsoptics.com
or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.



Copyright © 2024 OFS Fitel, LLC.
All rights reserved, printed in USA.

OFS Marketing Communications
DOC ID: fap-411 Date: 04/24

For a full list of our certifications, visit our website.



Sherpa CMS is a trademark of OFS Fitel, LLC. OFS reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.