




Standard POE (Point-of-Entry) Module

for InvisiLight® MDU Solution



Internal view of Standard POE Module

Features

- Allows termination of one of the fibers of the InvisiLight 4, 8, 12, or 16 Multifiber unit through direct connectorization or splicing (fusion or mechanical) to optical extensions (pigtailed) of two optical fibers
- Accommodates one internal optical adapter (SC footprint) and 2.1 meters of slack fiber
- An access point in each side allows cable access from the top of the module
- InvisiLight ILU or jumper output occurs from the base of the module through two access points, hidden underneath the cover

Benefits

- Compact dimensions
- Discreet appearance
- Easy to secure on the wall with two screws
- Internal fiber guides for easy installation
- Can be installed on any vertical plane surface
- Plastic body offers high mechanical resistance and an efficient design
- Accommodates splice protectors (40 mm)

Product Description

The Standard Point-of-Entry (POE) Module serves as the transition point between the building hallway and the customer living unit. Following an installation survey, the installer mounts this module on the exterior wall of each living unit. A fusion-spliced pigtail or mechanical connector connects the InvisiLight Multifiber Unit to the plug-and-play InvisiLight Indoor Living Unit (ILU) Solution. The Standard POE Module is part of the InvisiLight Multiple Dwelling Unit (MDU) Solution.



Standard POE Module Specifications

Product Characteristics

Capacity	2 splices 1 SCA adapter
Accessories	Screws and anchors
Application	Internal Use
Physical Characteristics	
Dimensions (H x W x D)	2.5 in. x 5.25 in. x 0.77 in. (63.50 mm x 133.35 mm x 19.56 mm)
Material	Polypropylene (PP), UL94V-0
Color	White (RAL 9016)
Standards	RoHS

Standard POE Module Ordering Information

Comcode	Part Number	Product Description
301107447	NVSLGHTHI-MODULE E/W LCA ADAPTER-PT	Point-of-entry (POE) module with LC-APC adapter and pigtail
301107454	NVSLGHTHI-MODULE E/W SCA ADAPTER-PT	Point-of-entry (POE) module with SC-APC adapter and pigtail
301107462	NVSLGHTH-Module E/W SPLICE TRAY	Point-of-entry (POE) module with splice tray, capacity for 12 fusion splices, no adapter



For additional information please contact your sales representative.

You can also visit our website at www.ofsoptics.com or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.



Copyright © 2023 OFS Fitel, LLC.
All rights reserved, printed in USA.

OFS Marketing Communications
Date: 05/23

InvisiLight is a registered trademark of OFS Fitel, LLC. OFS reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.

For a full list of our certifications, visit our website.

