



A Furukawa Company

TrueLase™ Optical Fibers

10/130 Passive LMA Double Clad Optical Fiber for Fiber Laser Applications



Features and Benefits

- Enables easy & efficient integration for monolithic fiber lasers and amplifiers
- Excellent fiber consistency and uniformity using OFS proprietary RE vapor phase delivery process
- TrueClad™ low index coating for extensive durability in sensitive environment and operating conditions

Applications

- Low power fiber lasers and amplifiers
- Lasers for marking
- Industrial, medical and military

Overview

Development of the new OFS TrueLase Optical Fiber family was driven by an increasing demand for a reliable fiber supply in the rapidly growing fiber laser market space. Fiber lasers had their start in the erbium doped amplification work done in the early 1990's. OFS, a global market leader in the design and manufacture of Erbium-Doped Optical Fibers, possesses the expertise and experience in fiber fabrication technology necessary to meet that demand. OFS has been developing and manufacturing high power components and modules for many years and understands the reliability standards expected in the diverse material processing applications.

The OFS family of TrueLase 10/130 Active and Passive LMA Double Clad Optical Fibers is an ideal tool for integrated low power fiber lasers and amplifiers. Our fibers combine high clad absorption, precision matched mode field diameter designs, and unprecedented manufacturing control ensuring easy integration across the entire laser architecture. All TrueLase optical fibers utilize the latest TrueClad low index polymer coating specially engineered to ensure superior reliability & performance in the most demanding of environments.



A Furukawa Company

LMA10-130	
Optical Specifications	
Background loss (@ 1150 nm)	<10 dB/km
Cladding loss (@ 1100 nm)	<10 dB/km
Cladding numerical aperture	≥0.46
Core numerical aperture (NA)	0.075 ± 0.005
LP ₀₁ MFD (@ 1070 nm)	11 ± 0.8 μm
Cladding absorption (@ 915 nm)	Not Applicable
Physical and Material Parameters	
Core concentricity error	<0.3 μm
Cladding diameter	130 ± 3 μm
Coating outside diameter	250 ± 15 μm
Cladding non-circularity	<0.5%
Coating type	TrueClad low index coating
Fiber geometry	Round
Performance	
Proof test	100 kpsi
Fiber efficiency (with respect to 1W launched power)	Not Applicable
Ordering Information	
Item #	79542



Copyright © 2016 OFS Fitel, LLC.
All rights reserved, printed in USA.

TrueClad and TrueLase are trademarks of OFS Fitel, LLC.
OFS reserves the right to make changes to the prices and product(s) described in this document at any time without notice. This document is for informational purposes only and is not intended to modify or supplement any OFS warranties or specifications relating to any of its products or services.

OFS Marketing Communications
Date: 12/16

For additional information please contact your sales representative.

You can also visit our website at www.ofsoptics.com or call 1-888-fiberhelp (1-888-342-3743) USA or 1-770-798-5555 outside the USA.